

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 4: A62B 18/02		(11) International Publication Number: (43) International Publication Date:	WO 87/ 01950 9 April 1987 (09.04.87)
(21) International Application Number: PCT/GI (22) International Filing Date: 26 September 1986	•	Suite 301, Sunlight House, C	Birch; Marks & Clerk, Quay Street, Manchester

(31) Priority Application Number:

8523795

(32) Priority Date:

26 September 1985 (26.09.85)

(33) Priority Country:

GB

(71) Applicant (for all designated States except US): PROTECTOR SAFETY LIMITED [GB/GB]; Great George Street, Wigan, Greater Manchester WN3 4DE (GB).

(72) Inventor; and


(75) Inventor/Applicant (for US only): FEENEY, John, Robert [GB/GB]; Protector Safety Limited, Great George Street, Wigan, Greater Manchester WN3 4DE (GB).

(81) Designated States: AT, AT (European patent), AU, BB, BE (European patent), BG, BR, CF (OAPI patent), CG (OAPI patent), CH, CH (European patent), CM (OAPI patent), DE, DE (European patent), DK, FI, FR (European patent), GA (OAPI patent), GB, GB (European patent), UK (OAPI patent), UK, UK, KP, KR, LK, LU, LU (European patent), MC, MG, ML (OAPI patent), MR (OAPI patent), MW, NL, NL (European patent), NO, RO, SD, SE, SE (European patent), SN (OAPI patent), SU, TD (OAPI patent), TG (OAPI patent), US.

Published

With international search report.

(54) Title: RESPIRATOR



(57) Abstract

A respirator having a cup-like body (7) associated with an air inlet (8) and an air outlet (9) and having a peripheral sealing element (2) shaped for location across the nose and around the mouth of a wearer wherein the sealing element (2) is located in position by a clamping element (3) which is releasably secured to the cup-like body (7).

## FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

	·					
AT AU BB BE BG BJ CF CG CH CM DE DK FI	Austria Australia Barbados Belgium Bulgaria Benin Brazil Central African Republic Congo Switzerland Cameroon Germany, Federal Republic of Denmark	FR GA GB HU IT JP KP KR LI LK LU MC MG	France Gabon United Kingdom Hungary Italy Japan Democratic People's Republic of Korea Republic of Korea Liechtenstein Sri Lanka Luxembourg Monaco Madagascar	ML MR MW NL NO RO SD SE SN SU TD TG US	Mali Mauritania Malawi Netherlands Norway Romania Sudan Sweden Senegal Soviet Union Chad Togo United States of America	

10

20

25

30

35

- 1 -

### RESPIRATOR

The present invention relates to a respirator and more particularly (but not exclusively) to those respirators known as half-mask respirators which are intended to cover only the nose and mouth of a wearer.

Most conventional half-mask respirators are moulded from natural rubber or other similar material (synthetic rubber, silicone rubber, PVC etc.). With this type of mask the face seal is effected by the part of the mask in contact with the face. To achieve this it is usual to have a reflex edge in which region the moulding is thinner and more flexible.

Other masks use an inflatable seal against the face and this may be combined with a rubber mask or a rigid plastic mask.

With the conventional masks, it may not be possible to replace the seal easily once it has lost its effectiveness due to repeated use of the mask which must therefore be discarded.

It is an object of the present invention to obviate or mitigate the above disadvantage.

'According to the present invention there is provided a respirator having a cup-like body associated with an air inlet and an air outlet and having a peripheral sealing element shaped for location across the nose and around the mouth of a wearer, wherein the sealing element is located in position by a clamping element which is releasably secured on the cup-like body.

Preferbly, the cup-like body and clamping element each have flanges which come into face-to-face clamping relationship when the clamping element is mounted on the body, and the seal has a

10

15

20

25

skirt or the like which is clamped between these flanges to retain the seal in position.

The invention will be further described by way of example only with reference to the accompanying drawings in which:

Fig. 1 is an exploded perspective view of one embodiment of half-mask respirator in accordance with the invention;

Fig. 2 is an exploded, part-sectional side view of the mask shown in Fig. 1, but omitting details of the harness; and

Fig. 3 is a side view of the assembled mask.

The illustrated half-mask respirator comprises a cup-like body 1 shaped for location over the nose and mouth of a user, a cushion-like face seal 2 for location on the cup 1, an outer clamping element 3, a standard filter cartridge 4, an inhalation valve 18 (not shown in Fig. 1, but clearly illustrated in Fig. 2), exhalation valves 5 (only one shown), and harness straps 6.

Cup 1 is a rigid plastic moulding formed as a cup-shaped body 7 having an aperture 8 in a flat frontal face thereof and two apertures 9 in a flat basal face thereof. Aperture 8 is extended inwardly by an internally screw-threaded tubular projection 8a in which an air inlet valve 18 (see Fig. 2) is located. Projecting laterally from the rim of the body 7 is an integral flange 10.

Clamping element 3 is also a rigid plastics
moulding and comprises a wall 11 with a stand-off
guard portion 12. More particularly, wall 11 is
shaped to be a close fit around the body 7 save that
the guard portion 12 will stand slightly clear of the
flat basal face of body 7 to allow the exhaust valves
5 to be positioned in apertures 9. The basal surface

. 10

20

25

30

35

of guard portion 12 is slotted so as to allow passage of air from valves 5.

Also provided on clamping element 3 is a flange 13 integral with the wall ll. Finally, stud-like projections 14 are provided on wall ll.

Complimentary snap-fit formations (not shown) are provided on the wall 11 of clamping element 3 and on the body 7 of cup 1 whereby clamping element 3 is a snap fit on cup 1. The snap fit formations may take a number of forms. For example, the cup-like body 7 may have a continuous or discontinuous undercut in which a complimentary projection on the inner surface of wall 11 locates. With element 3 snap-fitted on cup 1, the flanges 10 and 13 are in face-to-face clamping relation.

Face seal 2 is of the form illustrated in Fig. 1. More particularly the ring is shaped for location on, and around, the flange 10 of cup 1. Seal 2 is formed of a core ring of soft foam-rubber 15 clad with flexible PVC 16, such that seal 2 is of cushion-like construction. This PVC cladding 16 has a skirt 17 (the purpose of which will be described) provided around the inner periphery of the ring-like face seal body and extending inwardly thereof. The width of skirt 17 is substantially the same as that of flanges 10 and 13.

Assembly of the half-mask is as follows, it being assumed that inlet valve 18 and outlet valves 5 have been located in position.

Firstly, face-seal 2 is mounted on the cup 1 by manipulating the skirt 17 of seal 2 such that it overlies flange 10 of cup-like body 1. With the seal 2 so mounted on cup 1, a substantial part of the seal's ring like body is located on the side of flange 10 remote from the cup-shaped body 7.

20

. 25

30

Next, clamping element 3 is snap-fitted onto cup 1 thus ensuring that skirt 17 is securely clamped between flanges 10 and 13 thereby fixing seal 2 in position. With clamping element 3 located in position, guard portion 12 serves to protect valves 5 whilst allowing passage of air from the valves 5.

Assembly is completed by screwing cartridge 4 into projection 8a and finally attaching harness straps 6 to stude 14.

The assembled mask is of course worn with the seal 2 locating over the bridge of the nose and around the mouth of a wearer, the mask being supported in position by the harness straps 6 locating around the back of the wearers head. When the mask is worn, these harness straps 6 'pull' the clamping element 3 towards the face of the wearer thus enhancing the clamping action.

During inhalation, air is drawn through (and thus filtered by) the cartridge 4. Exhaled air is exhausted <u>via</u> the outlet valves 5.

It is inevitable that seal 2 will effectiveness after repeated usage of the mask. the illustrated mask construction, the seal may be replaced quickly and easily by releasing and removing clamping element 3 from cup 1 (after removal cartidge 4 if necessary), removing the old fitting a new one, and re-assembling Consequently there is no need to dispose of the mask once the seal loses its effectiveness.

The illustrated mask has a cushion-like seal. Other types of seal could however be used, e.g. inflatable seals or reflex-edge seals.

1

#### CLAIMS:

- 1. A respirator having a cup-like body associated with an air inlet and an air outlet and having a peripheral sealing element shaped for location across the nose and around the mouth of a wearer wherein the sealing element is located in position by a clamping element which is releasably secured to the cup-like body.
- 2. A respirator as claimed in claim 1 wherein the cup like body has a cup for location over the mouth and across the nose of a wearer and a first flange extending around the periphery of the cup said clamping element locates around the cup and has a second flange, and a portion of said sealing element is clamped between said first and second flanges.
  - 3. A respirator as claimed in claim 2 wherein the cup has a front face having an aperture therein, said aperture being extended by an inwardly directed tubular projection forming the air inlet and in which is provided an inhalation valve.
  - 4. A respirator as claimed in claim 3 wherein a filter cartridge is supported in said tubular projection.
  - 5. A respirator as claimed in claim 2 wherein the cup has a flat basal surface having at least one aperture in which is located an exhalation valve.
  - 6. A respirator as claimed in claim 5 wherein the clamping element has a guard portion for protecting the exhalation valve.
  - 7. A respirator as claimed in any one of claims 1 to 6 wherein the clamping element and the cup like body have complimentary snap fit formations for effecting said releasable securement.
    - 8. A respirator as claimed in any one of claims

20

25


- l to 7 wherein the sealing element comprising a ring of soft foam rubber clad with a flexible plastics material.
- 9. A respirator as claimed in claim 8 wherein the flexible plastics material is PVC.
- 10. A respirator as claimed in any one of claims 1 to 9 wherein the clamping element is provided with studs for the securement thereto of a harness for location around the back of the head of a wearer of the mask.

10


5

20

. 25



#### SUBSTITUTE SHEET



SUBSTITUTE SHEET

## INTERNATIONAL SEARCH REPORT

International Application No PCT/GB 86/00576

I. CLASSIF	FICATION	OF SUBJECT MATTER (if several classific	ation symbols apply, indicate all) <sup>16</sup>			
According to	o Internatio	nal Patent Classification (IPC) or to both Nation		·		
IPC":	A 62	B 18/02				
II. FIELDS	SEARCH					
		Minimum Documents		·		
Classification	System	CI	lassification Symbols			
IPC <sup>4</sup>		A 62 B		_		
		Documentation Searched other the to the Extent that such Documents a	an Minimum Documentation are included in the Fields Searched •	-		
	-			()		
			•			
		<u> </u>		·		
	MENTS C	ONSIDERED TO BE RELEVANT® on of Document, 11 with indication, where appro	portete of the relevant passages 12	Relevant to Claim No. 13		
Category *	Citatio	on of Document, " with indication, where appro	opnate, or the relevant passages			
Y,Y	DE,	<pre>C, 207751 (WESTFALIA see page 1; figures 1</pre>		1,2,3-7		
Y	US,	A, 2823671 (GARELICK, 1958, see column 2, 1 line 46; figures 1,5	, 2823671 (GARELICK, J.J.) 18 February 958, see column 2, line 23 - column 3, ine 46; figures 1,5			
Α	US,	A, 2931356 (SCHWARZ, see column 3, lines 1	K.H.) 5 April 1960, 0-34; figures 3,4	1,8		
A	us,	A, 3545436 (HOLLOWAY, 1970	R.L.) 8 December			
Α.	DÉ,	C, 334138 (DRAEGER, A	A.B.) 9 March 1921			
A	DE,	C, 702315 (AUERGESELI 1936	SCHAFT) 22 January			
		(1)				
		•				
"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention filing date "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)  "O" document referring to an oral disclosure, use, exhibition or other means  "P" document published prior to the international filing date but later than the priority date claimed  "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention  "X" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combined with one or more other such documents, such combined with one or more other such documents, such combined with one or more other such documents, such combined with one or more other such documents, such combined with one or more other such documents, such combined with one or more other such documents, such combined with one or more other such documents."  "E" later document published after the international filing date and not in conflict with the application but cited to understand the principle or theory underlying the invention.  "X" document of particular relevance; the claimed invention cannot be considered to involve an inventive atep when the document is combined with one or more other such documents, such combination being obvious to a person skilled invention.  "A" document means of particular relevance; the claimed invention or cannot be considered to involve an inventive atep when the document is combined with one or more other such document is combined with one or more other such documents.						
l ————	IFICATIO					
į .		ompletion of the international Search	Date of Mailing of this International S	Search Report		
		mber 1986	2 2 JAN 1987 Signature of Authorized Officers J			
internation	•	ng Authority PEAN PATENT OFFICE	I.I. VAN MOL	0		

Form PCT/ISA/210 (second sheet) (January 1985)

# ANNEX TO THE INTERNATIONAL SEARCH REPORT ON

INTERNATIONAL APPLICATION NO.

PCT/GB 86/00576 (SA

14685)

This Annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on 18/12/86

The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)	Publicatio date	
DE-C- 207751		None		
US-A- 2823671		None		
US-A- 2931356		None		
US-A- 3545436	08/12/70	None		
DE-C- 334138	***************************************	None		
DE-C- 702315		None		

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82